ECOFLEX 4M VÄRMEKABEL 15W/M MED MITTERMOSTAT

Lågeffektsvärmekabel 15w/m för rör och slang

15w Effekt 15 w +3° Tillslag vid 3C



En 4m värmekabel med 15/m mitt-termostat underlättar temperaturstyrd avledning av vatten i rör och slang. Termostaten sitter vid övergången mellan anslutningskabel och varmkabel och

CLIMACO

Cookiebot by Usercentrics

Consent | Details | About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary

Preferences

Statistics

Marketing


Allow selection

Allow all

Enkel och flexibel installation

För in värmekabeln i slangadaptern på dräneringstråget. (För gummitätningen som redan sitter på kabeln till termostaten.) Dra igenom hela kabeln i adaptern, peta kabeln ände till rätta med din mejsel i början. Trä slangklämman på slangen. För draglinan genom slangen. Tejpa fast värmekabeln i draglinan (2–3 tejpningar nära kabeländen, med en dm mellanrum). Smörj kabeländen och slangens öppning med lite diskmedel. Dra försiktigt kabeln genom slangen. Ta bort tejpen när den är igenom.





Vad ingår?



ClimaLine Ecoflex heatable with



ClimaLine Ecoflex heatable with

CLIMACO

Cookiebot by Usercentrics

Consent | Details | About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary

Preferences

Statistics

Marketing

Överblick

För	Frostfritt i slang - rör	Stickkontakt	Schuko, jordad
Uppvärmning	Värmekabel	Spänning	220-240 v 50-60 Hz
Termostatstyrd	Tillslag +3°C	Max effekt (w)	60
Färg	Vit, Svart		
Material	Silicon gummi		

På climaco.com får du veta hur man gör och vad du behöver

CLIMACO

Cookiebot by Usercentrics

Consent | Details | About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary

Preferences

Statistics

Marketing